



## ZK2000-5353-0xxx | Sensor cable, PUR, 5 x 0.34 mm<sup>2</sup>, drag-chain suitable

M12, plug, angled, male, 5-pin, A-coded – M12, plug, angled, male, 5-pin, A-coded

### Plugs



Electrical data	Head A	Head B
Rated voltage	60 V (according to IEC 61076-2-101)	60 V (according to IEC 61076-2-101)
Rated current	4 A at 40 °C (according to IEC 61076-2-101)	4 A at 40 °C (according to IEC 61076-2-101)
Shielding	no	no
Contact resistance	< 10 mΩ	< 10 mΩ
Insulation resistance	≥ 10 GΩ (according to IEC 60512-2)	≥ 10 GΩ (according to IEC 60512-2)
Mechanical data		
Installation size	M12	M12
Connector type	plug	plug
Configuration	angled	angled
Contact type	male	male
Number of positions (face)	5-pin	5-pin
Coding	A-coded	A-coded
Recommended torque, nut	0.6 Nm	0.6 Nm
Mating cycles	≥ 100 (according to IEC 60512-9a)	≥ 100 (according to IEC 60512-9a)
Way of locking	screw	screw
Weight per piece	0.023 kg (0.0507 lb)	0.023 kg (0.0507 lb)
Body colour	black	black
Body material	TPU, UL 94 HB	TPU, UL 94 HB
Coupling nut material	GD-Zn, Ni	GD-Zn, Ni
Seal	FPM	FPM
Contact carrier colour	red	red
Contact carrier material	PA, UL 94 V-0	PA, UL 94 V-0
Contact material	CuZn, Ni b/Au 0.2 gal.	CuZn, Ni b/Au 0.2 gal.
Environmental data		
Special features	halogen-free, flame-resistant as per IEC 60332-1-2, oil-resistant as per DIN EN 60811-2-1	halogen-free, flame-resistant as per IEC 60332-1-2, oil-resistant as per DIN EN 60811-2-1
RoHS compliant	yes	yes
Ambient temperature (operation)	-25...+80 °C, -13...+176 °F	-25...+80 °C, -13...+176 °F

Protection class	IP 65/67 in screwed condition (according to IEC 60529)	IP 65/67 in screwed condition (according to IEC 60529)
Pollution level	3/2 (according to IEC 60664-1)	3/2 (according to IEC 60664-1)

## Cable

Electrical data	
Rated voltage	60 V (according to IEC 61076-2-104)
Insulation resistance	$\geq 1 \text{ G}\Omega \cdot \text{km}$
Wire resistance (signal/24V)	$\leq 58.0 \text{ }\Omega/\text{km}$ (20 °C)
Test voltage	$\geq 3000 \text{ V}$
Mechanical data	
Conductor construction (signal/24V)	42 x 0.10 mm
Cross section (signal)	5 x 0.34 mm <sup>2</sup> (AWG22)
Min. bending radius, moved	10 x outer cable diameter
Min. bending radius, fixed installation	5 x outer cable diameter
Weight	37 kg/km (24.86 lb/1000 ft)
Outer cable diameter	5.1 mm $\pm$ 0.15 mm (0.200787" $\pm$ 0.0059")
Shielding	no
Use	drag-chain suitable
Max. acceleration	10 m/s <sup>2</sup>
Max. speed	3 m/s
Max. travel distance	10 m
Max. number of cycles	4 million
Wall thickness of wire insulation (signal/24V)	$\geq 0.21 \text{ mm}$
Jacket colour	black
Material jacket	PUR (polyurethane)
Wire colour code	brown, white, blue, black, grey
Printing colour	white
Environmental data	
Operation temperature range, moved	-25...+80 °C, -13...+176 °F
Operation temperature range, fixed installation	-40...+80 °C, -40...+176 °F
Flame-retardant	according to DIN EN 60332-2-2
Halogen-free	DIN VDE 0472 part 815
Approvals	UL

### Dimensions



A1	35.00 mm
A2	32.00 mm
B1	35.00 mm
B2	32.00 mm

## Notes

- Depending on the cable length (L), the following length tolerances apply:  
0 m...<0.2 m:  $\pm 10 \text{ mm}$  | 0.2...4.0 m:  $+ 40 \text{ mm}$  |  $\geq 4.0 \text{ m}$ :  $+ 1 \%$
- Illustrations similar
- Further cable length on request. The last three digits of the ordering information is the cable length in decimeters, e.g. ZKxxxx-xxxx-x020 = cable length 2.00 m

Ordering information	Length
ZK2000-5353-0010	1.00 m
ZK2000-5353-0030	3.00 m
ZK2000-5353-0050	5.00 m

Accessories	
ZB8801-0000	torque wrench for hexagonal plugs, adjustable
ZB8801-0002	torque cable key, M12/wrench size 13, for ZB8801-0000

Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2021

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.