

# ZS1020-0010 | IP-Link plug, plug for IP-Link system



## IP-Link, plug, straight



|                                 |                            |
|---------------------------------|----------------------------|
| <b>Electrical data</b>          |                            |
| <b>Mechanical data</b>          |                            |
| Accessories type                | Connectors                 |
| Installation size               | IP-Link                    |
| Connector type                  | plug                       |
| Configuration                   | straight                   |
| Way of locking                  | push-pull                  |
| Body color                      | black                      |
| Body material                   | Miramid FB30C, TPU 1195A   |
| Seal                            | FPM                        |
| <b>Environmental data</b>       |                            |
| Ambient temperature (operation) | -20...+70 °C, -4...+158 °F |
| Protection rating               | IP67                       |

|                   |  |
|-------------------|--|
| <b>Dimensions</b> |  |
|-------------------|--|

## Notes

- Illustrations similar

### Ordering information

|             |  |
|-------------|--|
| ZS1020-0010 | IP-Link plug, 1 piece, plug for IP-Link system |
|-------------|--|

### Accessories

|             |                                     |
|-------------|-------------------------------------|
| ZS5400-0001 | sanding gauge for IP-Link connector |
|-------------|-------------------------------------|

|             |                                |
|-------------|--------------------------------|
| ZS5400-0010 | abrasive paper P600, 10 sheets |
|-------------|--------------------------------|



Products marked with a crossed-out wheeled bin shall not be discarded with the normal waste stream. The device is considered as waste electrical and electronic equipment. The national regulations for the disposal of waste electrical and electronic equipment must be observed.

Beckhoff®, TwinCAT®, TwinCAT/BSD®, TC/BSD®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 07/2023

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.