





## ZS2000-1213 | M8 plug field assembly, sensor, IP 67

M8, plug, straight, male, 3-pin, A-coded

Electrical data	
Rated voltage	32 V
Rated current	4 A at 40 °C (according to IEC 61076-2-104)
Rated impulse voltage	1.5 kV
Shielding	no
Contact resistance	< 10 mΩ
Mechanical data	
Accessories Type	Connector
Installation size	M8
Connector type	plug
Configuration	straight
Contact type	male
Number of positions (face)	3-pin
Coding	A-coded
Wire termination	IDC
Recommended torque, nut	0.4 Nm
Mating cycles	≥ 100 (according to IEC 60512-9a)
Way of locking	screw
Weight per piece	0.028 kg (0.0617 lb)
Body colour	metal
Body material	Zinc diecast / PA
Coupling nut material	CuZn, Ni
Contact carrier colour	black
Contact carrier material	PA, UL 94
Contact plating	Au
Contact material	CuZn
Max. wire cross section	AWG26 ... AWG22 (0.14 mm <sup>2</sup> ... 0.34 mm <sup>2</sup> )
Max. cable outer diameter	2.5 - 5.1 mm
Environmental data	
RoHS compliant	yes
Ambient temperature (operation)	-40...+85 °C, -40...+185 °F
Protection class	IP 65/67 in screwed condition (according to IEC 60529)
Pollution level	3/2 (according to IEC 60664-1)

## Dimensions



A1	41.00 mm
A2	11.50 mm

## Notes

- Illustrations similar

<b>Ordering information</b>	
ZS2000-1213	Plug field assembly, Sensor, IP 67, M8, straight, male, 3-pin, A-coded, 0.14...0.34 mm <sup>2</sup> , Ø 3.5...5 mm

<b>Accessories</b>	
ZB8800	torque wrench for M8 cables with knurl, incl. ratchet
ZB8800-0002	torque wrench key for M8 (for field assembly) for ZB8800
ZB8801-0000	torque wrench for hexagonal plugs, adjustable

Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2021

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.